

Always. Reliable. Tight.



**hauff-  
technik®**

## Standard press seal with segmented ring technology

HRD150 SG 6x8-35 b40 A2/EPDM55

Article no.: 2700105000, GTIN: 4052487000192



- **Segmented ring technology for individual**
- **adjustment to cable diameters on site**

For sealing cables in core drills or wall sleeves. Split design for sealing new cables to be installed or cables that have already been laid.



Picture may differ from selected product

## FACTS

### Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

### Advantages:

- Empty openings are blind sealed ex works
- Split seal for retrofit installation
- Available from stock

### Scope of delivery:

- Blind plug
- Lubricating stick

## Dimensions:

- Sealing width: 40 mm
- Press plates: 5 mm

## Material:

- Press plates, screws, nuts and washers: rust-free stainless steel V2A (AISI 304L); (V4A (AISI 316L) on request)
- Rubber: EPDM

## Tightness:

- Gastight and watertight

## FEATURES

|                                        |        |
|----------------------------------------|--------|
| Wall sleeve/core drilled hole ID (mm): | 150    |
| Number of cables overall:              | 6      |
| Number of cables:                      | 6      |
| Cable OD (mm):                         | 8 – 35 |

## PICTURES

